

Technical sheet :

# **EXTENSIBLE PLATFORM**

---



## **Benefits**

- Flexibility for people lifting applications.
- 2 different working widths available.
- Heavy duty and galvanized structure for an improved longevity.
- Non-slip metal floor.
- Expandable sides are independent.
- Fork sleeves for yard handling.

## **Technical characteristics**

- Capacity from 365 to 1000kg.
- Slewing platform + / - 90° on both sides.
- Legally approved for 3 persons.
- Overload sensor.
- Fork sleeves: 238mm x 100mm.



Capacities		NAC 2.45 / 5m 365 kg	NAC 2.45 / 5M 1000 kg	NAC 2.45 / 6M 365 kg
Capacity including people (kg)		365	1000	365
Number of people		3	3	3
Weight and dimensions				
Overall height (mm)	h17	1300	1300	1300
Width minimum (mm)		2450	2450	2450
Width maximum (mm)		5000	5000	6000
Length (mm)		2230	2230	2230
Depth (mm)	p5	1200	1200	1200
Overall weight (kg)		1020	1150	1210
Working Parameters				
Machine Equipment		Platform predisposition	Platform predisposition	Platform predisposition
Rotation 1		180	180	180
Hydraulic system		false	false	false

Machines compatibility		NAC 2.45 / 5m 365 kg	NAC 2.45 / 5M 1000 kg	NAC 2.45 / 6M 365 kg
Reference Number		-	788786	788784
MT 1440 A		-	X	X
MT 1440 HA		-	X	X
MT 1840 A		-	X	X
MT 1840 HA		-	X	X
MT-X 1440 A		-	X	X
MT-X 1840 A		-	X	X
Reference Number E-RECO		921309	921308	921310
MRT 1440 Easy T4 S1 400°		-	-	X
MRT 1440 Easy T4 S2 400°		-	-	X
MRT 1640 Easy T4 S1 360°		-	-	X
MRT 1640 Easy T4 S1 400°		-	-	X
MRT 1640 Easy T4 S2 360°		X	X	X
MRT 1640 Easy T4 S2 400°		-	-	X
MRT 1840 Easy T4 S1 360°		-	-	X
MRT 1840 Easy T4 S1 400°		-	-	X
MRT 1840 Easy T4 S2 360°		X	X	X
MRT 1840 Easy T4 S2 400°		X	X	X
MRT 2145 Easy T4 S1 360°		-	-	X
MRT 2145 Easy T4 S1 400°		-	-	X
MRT 2145 Easy T4 S2 360°		X	X	X
MRT 2145 Easy T4 S2 400°		X	X	X
MRT 2150 Privilege Plus		X	X	X
MRT 2470 Privilege Plus		X	X	X
MRT 2545 Easy T4 S1 360°		-	-	X
MRT 2545 Easy T4 S1 400°		-	-	X
MRT 2545 Easy T4 S2 360°		X	X	X
MRT 2545 Easy T4 S2 400°		X	X	X
MRT 2550 Privilege Plus		X	X	X
MRT 3050 Privilege Plus		X	X	X
MRT 3255 Privilege Plus		X	X	X
MRT-X 1440 Easy 400°		X	X	X
MRT-X 1640 Easy 360°		X	X	X
MRT-X 1640 Easy 400°		X	X	X
MRT-X 1840 Easy 360°		X	X	X
MRT-X 1840 Easy 400°		X	X	X
MRT-X 2145 Easy 360°		-	-	X
MRT-X 2145 Easy 400°		-	-	X
MRT-X 2150 Privilege Plus		X	X	X
MRT-X 2470 Privilege Plus		X	X	X
MRT-X 2545 Easy 360°		X	X	X

Machines compatibility	NAC 2.45 / 5m 365 kg	NAC 2.45 / 5M 1000 kg	NAC 2.45 / 6M 365 kg
MRT-X 2545 Easy 400°	X	X	X
MRT-X 2550 Privilege Plus	X	X	X
MRT-X 3050 Privilege Plus	X	X	X
MRT-X 3255 Privilege Plus	X	X	X



Siège Social

430 rue de l'Aubinière - 44150 Ancenis Cedex - France

Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508  
RCS Nantes